

3.5KW/7KW

PORTABLE EV CHARGER



6A~32A Adjustable



PRODUCT STRUCTURE



SOCKETS AND GUNS



5M/10M/15M
Total Length



Red CEE
16A/32A



Blue CEE
16A/32A



AU Plug
16A/32A



AU/NZ Plug
10A/15A



Swiss T13
10/13/16A



Schuko
10/13/16A



UK
10/13/16A



NEMA 5-15
15A

Adjustable current-satisfy demand



- 6A
- 8A
- 10A
- 13A
- 16A
- 25A
- 32A



LED power display light



SAFETY PROTECTION



Overload protection



Over current protection



Electrostatic protection



Over voltage protection



Leakage protection



Over charge protection



Short circuit protection



Temperature Protection



Lightning protection



Protection level: IP54



Ip55 Waterproof

WATERPROOF AND DUSTPROOF



Cope with all types of outdoor weather



FULL LINK TEMPERATURE MONITORING SYSTEM



When temperature

$\geq 85^{\circ}\text{C}$

Cut off within

0.2s



COMPRESSION MATERIAL



The shell is made of high strength imported PC material with strong compressive resistance and firm use



PRODUCT PARAMETERS



Exquisite and compact, Easy to carry



PRODUCT PARAMETER

Type 2

3.5KW/7KW

6A~32A Adjustable



Specification	3.5KW/7KW 1 Phase
Plug	CEE/SCHUKO/AU/UK/ NEMA/SWISS Plug
Charging Type	Type2 IEC62196-2
Current	6A~32A Adjustable
Voltage	200V~250V
Protection	IP65
Operating Temperature	-30°C to +55°C
Cable Length	5M/10M/15M
Leakage Protection	TypeB AC30mA+ DC6mA

GBT

3.5KW/7KW

6A~32A Adjustable



Specification	3.5KW/7KW 1 Phase
Plug	CEE/SCHUKO/AU/UK/ NEMA/SWISS Plug
Charging Type	GBT 20234
Current	6A~32A Adjustable
Voltage	200V~250V
Protection	IP65
Operating Temperature	-30°C to +55°C
Cable Length	5M/10M/15M
Leakage Protection	TypeB AC30mA+ DC6mA

USAGE SCENARIO

